

GMRN SERIES AIR COOLED NON-CYCLING DRYER SPECIFICATIONS

MODEL	CAPACITY	NUMBER OF MODULES	AVAILABLE VOLTAGES	REFRIGERATION SYSTEM				TOTAL SYSTEM KW/H	PSID	IN/OUT HEADER	DIMENSIONS INCHES			WEIGHT (LBS)
				COMPRESSOR		CONDENSER					HEIGHT	WIDTH	DEPTH	
				HP	KW/H	CFM	KW/H							
GMRN3300	3,300	2	208-230/3/60 460/3/60 575/3/60	9	19.55	22800	3.036	22.58	2.8	6" Flg	126	101	98	7615
GMRN4200	4,200	2		10	25.70	22800	3.036	28.73	2.9	8" Flg	126	101	98	7850
GMRN5000	5,000	2		12	29.57	22800	3.036	32.6	3.7	8" Flg	126	101	98	8062
GMRN5400	5,400	2		13.5	34.07	22800	3.036	37.11	4.1	8" Flg	126	101	98	8287
GMRN6400	6,400	3		10	38.55	34200	4.554	43.1	2.9	8" Flg	126	151	98	11125
GMRN7500	7,500	3		12	44.35	34200	4.554	48.91	3.7	8" Flg	126	151	98	11415
GMRN8100	8,100	3		13.5	51.11	34200	4.554	55.66	4.0	10" Flg	126	151	98	11815
GMRN8500	8,500	4		10	51.40	45600	6.072	57.47	2.9	10" Flg	126	202	98	15040
GMRN10000	10,000	4		12	53.14	45600	6.072	65.21	3.4	12" Flg	126	202	98	15670
GMRN10800	10,800	4		13.5	68.14	45600	6.072	74.22	4.0	12" Flg	126	202	98	16070
GMRN12500	12,500	5		12	73.92	57000	7.590	81.51	3.8	14" Flg	126	252	98	19755
GMRN13500	13,500	5		13.5	85.18	57000	7.590	92.77	4.1	14" Flg	126	252	98	20255

GMRN SERIES WATER COOLED NON-CYCLING DRYER SPECIFICATIONS

MODEL	CAPACITY	NUMBER OF MODULES	AVAILABLE VOLTAGES	REFRIGERATION SYSTEM				TOTAL SYSTEM KW/H	PSID	IN/OUT HEADER	DIMENSIONS INCHES			WEIGHT (LBS)
				COMPRESSOR		CONDENSER					HEIGHT	WIDTH	DEPTH	
				HP	KW/H	GPM	CONN.							
GMRN4100	4,100	2	208-230/3/60 460/3/60 575/3/60	9	17.86	26.1	2" NPT	17.86	3	6" Flg	101	101	98	6865
GMRN4800	4,800	2		10	23.21	29.8	2" NPT	23.21	3.3	8" Flg	102	101	98	7100
GMRN5500	5,500	2		12	27.27	31.7	2" NPT	27.27	4.1	8" Flg	102	101	98	7312
GMRN7200	7,200	3		10	34.81	44.7	2" NPT	34.81	3.3	8" Flg	102	151	98	10150
GMRN8200	8,200	3		12	40.91	47.5	2" NPT	40.91	4.1	8" Flg	102	151	98	10440
GMRN9600	9,600	4		10	46.41	59.6	2" NPT	46.41	3.3	10" Flg	104	202	98	13740
GMRN11000	11,000	4		12	54.54	63.3	2" NPT	54.54	4.1	12" Flg	105	202	98	14370
GMRN12000	12,000	5		10	58.02	74.5	2" NPT	58.02	3.3	14" Flg	106	252	98	17620
GMRN13750	13,750	5		12	68.18	79.2	2" NPT	68.18	4.1	14" Flg	106	252	98	18130

Capacity reflects SCFM at 100 PSIG, 100°F inlet conditions & 100°F ambient.
 Inlet/outlet connections are 150# ANSI RF flanges.
 Watts specified assume 35°F evaporator and 100°F ambient at full load conditions.
 Dimensions are in inches. Dimensions and specifications are subject to change without notice.
 Condenser flow requirements on water cooled models are based on 85°F water.

