

EnviroAire Technical Data

FIXED SPEED MACHINES, 50 & 60 HZ

MODEL	COOLING METHOD	DRIVE MOTOR		NOMINAL PRESSURE		FAD*		NOISE LEVEL**	WEIGHT		DIMENSIONS L x W x H IN. (MM)
		HP	KW	PSIG	BAR	ACFM	M ³ /MIN		LBS	KG	
T75	Air	100	75	116	8	437	12.37	76	6,665	3,023	102.2 x 68.7 x 78.8 (2597 x 1744 x 2001)
	Water	100	75	145	10	383	10.85	75	7,105	3,223	
T90	Air	125	90	116	8	562	15.91	77	7,125	3,223	
	Water	125	90	145	10	464	13.14	76	7,546	3,423	
T110	Air	150	110	116	8	670	18.97	78	7,198	3,265	
	Water	150	110	145	10	596	16.88	78	7,639	3,465	
T132	Air	180	132	116	8	797	22.57	78	8,007	3,632	
	Water	180	132	145	10	741	20.98	77	8,007	3,632	
T160	Air	215	160	145	10	795	22.51	79	8,034	3,644	
	Water	215	160	145	10	795	22.51	78	8,475	3,844	
T165	Water	215	160	125	8.6	988	28.10	77	10,395	4,715	
T200	Water	270	200	145	10	875	24.80	79	11,155	5,060	
				125	8.6	1236	35.00	80			
T250	Water	335	250	145	10	1080	30.60	81	11,497	5,215	
				125	8.6	1525	43.20	81			
T315	Water	420	315	145	10	1366	38.70	82	12,170	5,520	
				125	8.6	1705	48.30	81			
				145	10	1585	44.90	82			

* Data measured and stated in accordance with ISO1217 4th Edition Annex C and E at the following conditions:
Air Intake Pressure: 1 bar a / 14.5 psi, Air Intake Temperature: 20°C / 68°F, Humidity: 0% (dry)

** Measured in free field conditions in accordance with the ISO 2151, tolerance ± 3 dB(A)