

# ELECTRA SAVER II G2 40-100 HP ROTARY SCREW COMPRESSOR, 60 HZ

MODEL	DRIVE MOTOR		NOMINAL PRESSURE		FAD		NOISE LEVEL* DB(A)	WEIGHT		DIMENSIONS L x W x H IN. (MM)
	HP	KW	PSIG	BAR	ACFM	M <sup>3</sup> /MIN		LBS	KG	
STG2-40	40	30	100	6.9	204	5.78	78	2098	952	
			125	8.6	192	5.44				
			150	10.3	162	4.59				
			175	12.0	148	4.19				
			200	13.8	137	3.88				
STG2-50	50	37	100	6.9	251	7.11	78	2164	982	70 x 52 x 47 (1778 x 1321 x 1194)
			125	8.6	233	6.6				
			150	10.3	213	6.03				
			175	12.0	191	5.41				
			200	13.8	170	4.82				
STG2-60	60	45	100	6.9	305	8.64	79	2404	1090	
			125	8.6	287	8.14				
			150	10.3	249	7.05				
			175	12.0	219	6.20				
			200	13.8	217	6.14				
STG2-75	75	55	100	6.9	411	11.64	81	4521	2051	
			125	8.6	365	10.39				
			150	10.3	305	8.64				
			175	12.0	263	7.45				
			200	13.8	261	7.39				
STG2-100	100	75	100	6.9	541	15.32	81	4660	2114	90 x 61 x 59 (2286 x 1549 x 1499)
			125	8.6	496	14.05				
			150	10.3	434	12.29				
			175	12.0	346	9.80				
			200	13.8	345	9.77				

\*Noise level, weights and dimensions are for unenclosed models.