

ELECTRA SAVER II 60-200 HP ROTARY SCREW COMPRESSOR

| MODEL | DRIVE MOTOR | | 50 Hz | | | | 60 Hz | | | | | | | |
|----------|-------------|-----|------------------|------|------|---------------------|------------------|------|-------|---------------------|--------------|--------|------|--------------------------------------|
| | HP | KW | NOMINAL PRESSURE | | FAD | | NOMINAL PRESSURE | | FAD | | NOISE LEVEL* | WEIGHT | | DIMENSIONS L x W x H IN. (MM) |
| | | | PSIG | BAR | ACFM | M ³ /MIN | PSIG | BAR | ACFM | M ³ /MIN | | LBS | KG | |
| ST-60 | 60 | 45 | 100 | 6.9 | 260 | 7.37 | 100 | 6.9 | 279 | 7.90 | 88 | 3370 | 1529 | 90 x 55 x 56 (2286 x 1397 x 1422) |
| | | | 125 | 8.6 | 193 | 5.47 | 125 | 8.6 | 234 | 6.63 | | | | |
| | | | 150 | 10.3 | 190 | 5.38 | 150 | 10.3 | 202 | 5.72 | | | | |
| | | | 175 | 12.0 | N/A | N/A | 175 | 12.0 | 200 | 5.67 | | | | |
| | | | 200 | 13.8 | N/A | N/A | 200 | 13.8 | 163 | 4.62 | | | | |
| ST-75 | 75 | 55 | 100 | 6.9 | 361 | 10.23 | 100 | 6.9 | 355 | 10.06 | 88 | 3370 | 1529 | |
| | | | 125 | 8.6 | 320 | 9.07 | 125 | 8.6 | 320 | 9.07 | | | | |
| | | | 150 | 10.3 | 255 | 7.22 | 150 | 10.3 | 273 | 7.73 | | | | |
| | | | 175 | 12.0 | N/A | N/A | 175 | 12.0 | 232 | 6.57 | | | | |
| | | | 200 | 13.8 | N/A | N/A | 200 | 13.8 | 226 | 6.40 | | | | |
| ST-100 | 100 | 75 | 100 | 6.9 | 475 | 13.46 | 100 | 6.9 | 495 | 14.02 | 88 | 3625 | 1644 | |
| | | | 125 | 8.6 | 410 | 11.61 | 125 | 8.6 | 450 | 12.75 | | | | |
| | | | 150 | 10.3 | 390 | 11.05 | 150 | 10.3 | 350 | 9.92 | | | | |
| | | | 175 | 12.0 | N/A | N/A | 175 | 12.0 | 347 | 9.83 | | | | |
| | | | 200 | 13.8 | N/A | N/A | 200 | 13.8 | 316 | 8.95 | | | | |
| ST-125 | 125 | 90 | 100 | 6.9 | 610 | 17.28 | 100 | 6.9 | 620 | 17.56 | 88 | 4804 | 2179 | |
| | | | 125 | 8.6 | 500 | 14.16 | 125 | 8.6 | 537 | 15.21 | | | | |
| | | | 150 | 10.3 | 428 | 12.12 | 150 | 10.3 | 485 | 13.74 | | | | |
| | | | 175 | 12.0 | N/A | N/A | 175 | 12.0 | 343.5 | 9.73 | | | | |
| | | | 200 | 13.8 | N/A | N/A | 200 | 13.8 | 339.5 | 9.62 | | | | |
| ST-150 | 150 | 110 | 100 | 6.9 | 734 | 20.79 | 100 | 6.9 | 750 | 21.25 | 88 | 5111 | 2318 | |
| | | | 125 | 8.6 | 637 | 18.05 | 125 | 8.6 | 618 | 17.51 | | | | |
| | | | 150 | 10.3 | 632 | 17.90 | 150 | 10.3 | 529 | 14.99 | | | | |
| | | | 175 | 12.0 | N/A | N/A | 175 | 12.0 | 481.5 | 13.64 | | | | |
| | | | 200 | 13.8 | N/A | N/A | 200 | 13.8 | 477 | 13.51 | | | | |
| ST-200** | 200 | 150 | 100 | 6.9 | | | 100 | 6.9 | 750 | 21.25 | 88 | 5479 | 2485 | |
| | | | 125 | 8.6 | N/A | N/A | 125 | 8.6 | 744 | 21.08 | | | | |
| | | | 150 | 10.3 | | | 150 | 10.3 | 732 | 20.74 | | | | |
| | | | 175 | 12.0 | | | 175 | 12.0 | 713 | 20.20 | | | | |
| | | | 200 | 13.8 | | | 200 | 13.8 | 582 | 16.49 | | | | |
| ST-200 | 200 | 150 | 100 | 6.9 | 817 | 23.14 | 100 | 6.9 | 1000 | 28.33 | 88 | 6328 | 2870 | |
| | | | 125 | 8.6 | 701 | 19.86 | 125 | 8.6 | 875 | 24.79 | | | | |

*Noise level, weights and dimensions are for unenclosed models.

**100, 110, 125 psig available as field set option only.