

### Decades of Dependability

The engineering ingenuity of Gardner Denver began in 1859. For over 150 years, our compressed air products have been a dependable resource for meeting the world's most demanding and everchanging industrial needs. Featuring direct drive and premium efficiency motors, the Electra Saver® compressors provide the most durable and efficient drive train money can buy.

### **Bigger is Better**

Featuring super-sized bearings and up to 40% larger airends than the competition, the Electra Saver® is not only bigger, it is better. The larger airends, running at slower speeds, maximize efficiency and reduce mechanical wear and tear, while the permanent alignment of the airend and motor ensure maximum coupling and bearing life.

### Leading in Energy Savings

Over 40 years ago, Gardner Denver introduced the patented Turn Valve<sup>™</sup> technology - the most efficient part load capacity control system in the industry. With infinite positions in an operating range of 40% to 100% capacity, compressor efficiency is maximized because the Turn Valve<sup>™</sup> airend compresses only the volume of air required without affecting the built-in compression ratio at partial load conditions. This technology eliminates wide pressure fluctuations and massive storage requirements. Backed by proven reliability, the simple design eliminates complicated electronics and intricate valving. Shatter the competition with energy savings and reliability when you choose an Electra Saver<sup>®</sup> from Gardner Denver.



# ELECTRA SAVER 350-500 HP ROTARY SCREW COMPRESSOR

| MODEL   | DRIVE<br>MOTOR |     | 50 Hz               |                    |                      |                         | 60 Hz               |                    |                      |                         |                     |       |      |                                       |
|---------|----------------|-----|---------------------|--------------------|----------------------|-------------------------|---------------------|--------------------|----------------------|-------------------------|---------------------|-------|------|---------------------------------------|
|         |                |     | NOMINAL<br>PRESSURE |                    | FAD                  |                         | NOMINAL<br>PRESSURE |                    | FAD                  |                         | NOISE<br>LEVEL' WEI |       | IGHT | DIMENSIONS<br>L × W × H               |
|         | HP             | КW  | PSIG                | BAR                | ACFM                 | M³/MIN                  | PSIG                | BAR                | ACFM                 | M³/MIN                  | DB(A)               | LBS   | KG   | IN. (MM)                              |
| SAV-350 | 350            | 260 | 100<br>125<br>150   | 6.9<br>8.6<br>10.3 | 1800<br>1390<br>1120 | 50.99<br>39.38<br>31.73 | 100<br>125<br>150   | 6.9<br>8.6<br>10.3 | 1684<br>1434<br>1166 | 47.71<br>40.62<br>33.03 | 84                  | 14200 | 6441 | 153 × 84 × 78<br>(3886 × 2134 × 1981) |
| SAV-400 | 400            | 298 | 100<br>125<br>150   | 6.9<br>8.6<br>10.3 | 2070<br>1670<br>1310 | 56.64<br>47.31<br>37.11 | 100<br>125<br>150   | 6.9<br>8.6<br>10.3 | 1943<br>1652<br>1414 | 55.04<br>46.80<br>40.06 |                     | 14500 | 6577 |                                       |
| SAV-500 | 500            | 373 | 100<br>125<br>150   | 6.9<br>8.6<br>10.3 | 2580<br>2050<br>1700 | 73.09<br>58.07<br>48.16 | 100<br>125<br>150   | 6.9<br>8.6<br>10.3 | 2459<br>2118<br>1634 | 69.66<br>60.00<br>46.29 |                     | 15000 | 6804 |                                       |

1) Noise level, weights and dimensions are for unenclosed models.

## Electra Saver<sup>®</sup> Features (350–500 HP)

- Gear drive, oil flooded, single stage rotary screw air compressor
- AEON 9000SP
- Air and water-cooled
- AirSmart<sup>™</sup> microprocessor controller
- Oil cooler/aftercooler: Air-cooled models - heavy duty radiator-type with thermally controlled, totally enclosed fan motor with remote mount NEMA 1 starter; Watercooled models - heavy duty shell and tube heat exchangers
- cULus listed and CSA approved electronics
- Enclosure: Partial standard
- Automatic, integral Turn Valve™ part-load control system
- Package mounted moisture separator and trap
- Mounted main motor starter not available
- NEMA 4 electrical enclosure
- ODP main motor; optional TEFC main motor

- ASME coded oil reservoir
- Thermostatic oil control mixing valve
- Stainless steel control lines
- Minimum pressure discharge check valve
- Optional remote mounted air-cooled cooler
- Optional seacoast (air-cooled) or salt water (water-cooled) cooler
- Voltage: 460 / 575 V (3 phase only)

### Distributed by:-



Air Compressor Energy Systems, Inc. 6735 Brandt St, Romulus, MI 48174 800-242-3449

### www.aircompressorenergy.com





#### Gardner Denver, Inc.

1800 Gardner Expressway Quincy, IL 62305 866-440-6241 www.gardnerdenverproducts.com

©2016 Gardner Denver, Inc. Printed in U.S.A. GSCS-SAV-350-500 1st Ed. 5/16 Supersedes GS-SAV-350-500 4th Ed. 11/12

