



INDUSTRIAL | 10 HP ROTARY SCROLL AIR COMPRESSORS

EnviroAire S10

Gardner Denver EnviroAire compressors provide the reliable, high quality compressed air that you've come to expect from Gardner Denver. EnviroAire compressors offer a wide selection of configurations and top-quality available options. Gardner Denver designed this series specifically for industrial and laboratory applications that require 100% oil-less air. Experience proven results with Gardner Denver—the leader in durability, reliability and efficiency.

Standard Equipment

- Continuous operation, 100% duty cycle
- 5 Micron industrial grade intake air filter
- ASME coded receiver
- Premium efficient TEFC motor
- Unique tip seal design
- Low sound levels and vibration
- Re-greasable bearings
- Integral cooling fan
- Easy accessibility for maintenance
- 1-Year package warranty
- 1-Year airend warranty

Available Options

- Tank Sizes—30, 80, 120 or 240 gallon
 - Galvanized receiver
 - Vinyl (epoxy) lined receiver
- Electronic tank drain
- Mass. code fittings
- Starter
- High temp switch
- Dryer options
 - Refrigerated dryer
 - Desiccant dryer

Gardner
Denver

BARE AIREND

MODEL	DIMENSIONS L x W x H IN.	APPROX. SHIP WEIGHT LBS
SC10	16.8 x 16.8 x 13.9	62

SIMPLEX

MOTOR HP	BASE OR TANK CAPACITY GAL.	IDENTIFICATION NUMBER	DIMENSIONS L x W x H IN.	APPROX. SHIP WEIGHT LBS	116 PSI RATING		140 PSI RATING	
					RPM	ACFM	RPM	ACFM
10	Base	BENV10	38 x 21 x 17	375	3750	31.6	3216	25.3
10	30	HENV10-3	43 x 24 x 38	650	3750	31.6	3216	25.3
10	80	HENV10-8	67 x 24 x 42	775	3750	31.6	3216	25.3
10	120	HENV10-12	71 x 27 x 46	875	3750	31.6	3216	25.3

DUPLEX

MOTOR HP	BASE OR TANK CAPACITY GAL.	IDENTIFICATION NUMBER	DIMENSIONS L x W x H IN.	APPROX. SHIP WEIGHT LBS	116 PSI RATING		140 PSI RATING	
					RPM	ACFM	RPM	ACFM
10	Base	BENV10D	48 x 22 x 36.5	943	3750	63.2	3216	50.6
10	80	HENV10D-8	65 x 26 x 61.5	1340	3750	63.2	3216	50.6
10	120	HENV10D-12	69 x 27 x 65.5	1440	3750	63.2	3216	50.6
10	240	HENV10D-24	86 x 33 x 71.5	1660	3750	63.2	3216	50.6

Simplex CFM values are doubled for duplex units. Duplex units have two motors and two pumps on one base/tank.

TRIPLEX

MOTOR HP	BASE OR TANK CAPACITY GAL.	IDENTIFICATION NUMBER	DIMENSIONS L x W x H IN.	APPROX. SHIP WEIGHT LBS	116 PSI RATING		140 PSI RATING	
					RPM	ACFM	RPM	ACFM
10	Base	BENV10T	48 x 22 x 54.5	1407	3750	94.8	3216	75.9

Simplex CFM values are tripled for triplex units. Triplex units have three airends and three motors stacked on a common base.

QUADRAPLEX

MOTOR HP	BASE OR TANK CAPACITY GAL.	IDENTIFICATION NUMBER	DIMENSIONS L x W x H IN.	APPROX. SHIP WEIGHT LBS	116 PSI RATING		140 PSI RATING	
					RPM	ACFM	RPM	ACFM
10	Base	BENV10Q	48 x 22 x 72	1875	3750	126.4	3216	101.2

Simplex CFM values are quadrupled for Quadraplex units. Quadraplex units have four airends and four motors stacked on a common base.



Distributed by:-



Air Compressor Energy Systems, Inc.

6735 Brandt St, Romulus, MI 48174

800-242-3449

www.aircompressorenergy.com

Gardner Denver, Inc.

1800 Gardner Expressway

Quincy, IL 62305

866-440-6241

www.gardnerdenver.com/gdproducts



©2017 Gardner Denver, Inc. Printed in U.S.A.
GLCS-ENV-IND-S10 2nd Ed. 2/17

