

	REPLACEMENT MODEL GRADE-FEATURES	CAPACITY		CONNECTIONS NPT/ANSI FLG.	STANDARD FEATURES					MAX PRESSURE PSIG [KGF/CM <sup>2</sup> ] & TEMP °F (°C)		DIMENSIONS						ELEMENT		
		SCFM	M <sup>3</sup> /MIN		FILTER GRADES					MANUAL DRAIN	WITH D OR L	HEIGHT		WIDTH		WEIGHT		MODEL-GRADE	QTY	
					A	B	C,E,F	D	G			IN	MM	IN	MM	LB	KG			
MODULAR TYPE HOUSINGS	FIL12-11	20	0.57	¾" NPTF	A	A P	A P	P	NONE	300 psig 21 kgf/cm <sup>2</sup> 150°F 66°C	250 psig 17.6 kgf/cm <sup>2</sup> 150°F 66°C	8.15	207	4.13	105	4.2	1.9	FIL12-E	1	
	FIL14-13	35	1.00	½" NPTF								11.05	281	4.13	105	8.1	3.7	FIL14-E		
	FIL16-13	60	1.72	½" NPTF								13.4	340	4.13	105	8.5	3.9	FIL16-E		
	FIL18-15	100	2.9	¾" NPTF	A	A G	A G	G		15.32	389	5.25	133	6.3	2.9	FIL18-E				
	FIL20-17	170	4.9	1" NPTF						19.57	497	5.25	133	6.9	3.1	FIL20-E				
	FIL22-21	250	7.2	1½" NPTF	G		(1)	(1)		22.8	579	6.44	164	10.2	4.6	FIL22-E				
	FIL24-21	375	11	1½" NPTF	27.29	693				6.44	164	11.3	5.1	FIL24-E						
	FIL26-23	485	14	2" NPTF	(1)	G (1)	A G	G		31.08	789	7.63	194	28	12.7	FIL26-E				
	FIL28-25	625	18	2½" NPTF						36.83	935	7.63	194	33	15.0	FIL28-E				
	FIL30-25	780	22	2½" NPTF						42.96	1091	7.63	194	38	17.2	FIL30-E				
FIL32-27	625	18	3" NPTM	A	A G	A G	G	NONE (1)	300 psig 21 kgf/cm <sup>2</sup>	300 psig 21 kgf/cm <sup>2</sup>	40.88	1038	10.25	260	36	16.3	FIL32-E	1		
FIL34-27	1,000	29	3" NPTM	(1)	G (1)	G (1)			G	NONE (1)	225 psig 15.8 kgf/cm <sup>2</sup> 150°F 66°C	225 psig 15.8 kgf/cm <sup>2</sup> 150°F 66°C	48.00	1219	16.00	406	91	41.3	FIL34-E	2
FIL36-27	1,250	36	3" NPTM										48.00	1219	16.00	406	91	41.3	FIL32-E	
FIL38-27	1,875	54	3" NPTM										49.00	1245	16.25	413	120	54.4	FIL32-E	3
FIL40-29	2,500	72	4" FLG.										52.25	1327	20.00	508	179	81.2	FIL32-E	4
FIL42-29	3,125	89	4" FLG.										52.25	1327	20.00	508	182	82.6	FIL32-E	5
FIL44-31	5,000	143	6" FLG.										54.63	1387	24.00	610	271	123	FIL32-E	8
FIL46-31	6,875	197	6" FLG.										62.56	1589	28.00	711	518	235	FIL32-E	11
FIL48-31	8,750	250	6" FLG.										62.56	1589	28.00	711	527	239	FIL32-E	14
FIL50-33	11,875	340	8" FLG.										69.13	1756	33.00	838	709	322	FIL32-E	19
FIL52-33	16,250	465	8" FLG.				67.94	1726					39.00	991	918	416	FIL32-E	26		
FIL54-35	21,250	608	10" FLG.	70.94	1802	45.88	1165	1412	640	FIL32-E	34									

(1) Drain plugs standard. Externally mounted automatic drains are available.

A - Internal Automatic Drain; E - Electronic Demand Drain; P - Differential Pressure Slide; G - Differential Pressure Gauge; L - Liquid Level Indicator