



215-400 HP FIXED SPEED ROTARY SCREW COMPRESSORS

L-Series

Advanced Technology. Inspired Simplicity.

L-Series compressors from Gardner Denver feature more than just the latest compressor technology. They contain the cleanest, simplest, most intuitive machine layouts on the market. Equipped with standard TEFC main motors, wye-delta starters, GD Pilot TS™ microprocessor controllers and quiet enclosures, an L-Series unit from Gardner Denver is the optimal solution when a feature-rich, simple-to-operate compressor is required.

First Class Serviceability

The L-Series units set a new standard in serviceability. By utilizing integrated airend design techniques, Gardner Denver delivers unprecedented access to service and routine maintenance items. At the same time, the compact design eliminates unneeded connections and minimizes piping; reducing the opportunity for leaks. Couple these features with an intuitive touch screen controller with optional data logging and sequencing capabilities and you have a world class compressor package.

Gardner
Denver

L160-L290 ROTARY SCREW COMPRESSOR

MODEL	DRIVE MOTOR		50 Hz				60 Hz				NOISE LEVEL ²		WEIGHT		DIMENSIONS L x W x H IN. (MM)
	HP	KW	NOMINAL PRESSURE		FAD ¹		NOMINAL PRESSURE		FAD ¹		DB(A)	LBS	KG		
			PSIG	BAR	ACFM	M ³ /MIN	PSIG	BAR	ACFM	M ³ /MIN					
L160	215	160	110	7.5	1131.0	32.04	100	6.9	1118.8	31.68	78	9229	4186	115 x 82 x 86 (2921 x 2083 x 2184)	
			145	10.0	995.5	28.20	125	8.6	1031.3	29.20					
			190	13.0	844.0	23.91	190	13.0	811.4	22.98					
L200	270	200	110	7.5	1384.8	39.23	100	6.9	1326.6	37.56	79	9733	4415		
			145	10.0	1230.2	34.85	125	8.6	1255.7	35.56					
			190	13.0	1037.1	29.38	190	13.0	1000.1	28.32					
L250	335	250	110	7.5	1483.7	42.03	100	6.9	1451.6	41.10	80	10196	4625		
			145	10.0	1306.5	37.01	125	8.6	1385.8	39.24					
			190	13.0	1152.2	32.64	190	13.0	1149.2	32.54					
L290	400	290	110	7.5	1662.6	47.10	100	6.9	1601.7	45.35	81	10251	4650		
			145	10.0	1466.0	41.53	125	8.6	1532.7	43.40					
			190	13.0	1286.3	36.44	190	13.0	1231.9	34.88					

1) Data measured and stated in accordance with ISO1217, Ed. 4, Annex C & Annex E at the following conditions:

Air Intake Pressure 1 bar A, Air Intake Temperature 20° C, Humidity 0% (Dry)

2) Measured in free field conditions in accordance with ISO 2151, tolerance +/- 3 dB

L-Series Features (215-400 HP)

- Direct-gear drive, oil flooded, single stage rotary screw air compressor
- AEON 9000SP lubricant
- Air-cooled standard
- Air supply piping includes hard pipe design with Viton Victaulic couplings
- CRN and ASME rated aftercooler
- CSA labeled and approved electrical controls and wiring
- cUL labeled electronics (including C-UL-US open industrial control panel)
- GD Pilot TS™ microprocessor controller
- Integrated spin-on oil filters
- Integrated thermostatic thermal mixing valve
- IP54 electrical enclosure
- Load/no load control and timed shutdown
- Moisture separator (shipped loose)
- Mounted and wired wye-delta starter
- SD card for data logging
- Optional Base Load Selector sequencing
- Optional potential free contacts kit
- Optional Profibus interface module
- Quiet enclosure
- Second pressure band control for lead/lag operation
- TEFC main motor
- Two-stage air filter and air/oil separation system
- Voltage: 460 / 575V

Distributed by:-



Air Compressor Energy Systems, Inc.

6735 Brandt St, Romulus, MI 48174

800-242-3449

www.aircompressorenergy.com

**Gardner
Denver®**

Gardner Denver, Inc.

1800 Gardner Expressway

Quincy, IL 62305

866-440-6241

www.gardnerdenverproducts.com



©2016 Gardner Denver, Inc. Printed in U.S.A.

GSCS-L160-L290 1st Ed. 4/16

Please recycle after use.