

PRODUCT SPECIFICATIONS

DRYER MODEL	INLET FLOW		PRESSURE DROP PSI	VOLTAGE	IN/OUT CONNECTIONS	POWER CONSUMPTION KW	REFRIGERANT	HEIGHT		WIDTH		DEPTH		WEIGHT LBS
	NM ³ /H	SCFM						IN	MM	IN	MM	IN	MM	
RPC75	75	127	2.9	115/1/60	1" NPT	0.54	R134A	30	751	15	381	24	603	120
RPC100	100	170	3	115/1/60	1" NPT	0.62	R134A	28	711	15	381	31	781	147
RPC150	150	255	1.7	115/1/60	1" NPT	1.04	R407C	30	751	18	443	36	911	203
			3.6	230/1/60	2" NPT	0.85		30	751	18	443	36	911	189
RPC200	200	340	2.2	230/1/60	2" NPT	1.32	R407C	30	751	18	443	38	961	217
			2.1	460/3/60		1.26	R134A	30	751	18	443	38	961	244
RPC300	300	509	3.6	460/3/60	2" NPT	1.99	R407C	36	911	20	494	44	1111	324
RPC400	400	680	2.5	230/1/60	2" NPT	2.54	R407C	36	911	20	494	44	1111	335
RPC450	450	765	3.0	460/3/60	2" NPT	3.23	R407C	41	1032	20	494	50	1253	366
RPC550	550	935	3.0	460/3/60	2" NPT	3.42	R407C	41	1032	20	494	50	1253	396

Performance data presented in accordance with ISO 7183 (Option A2) conditions: 100°F inlet temperature, 100°F ambient temperature and 100 psig conditions.