

## ENGINE DRIVEN **GASOLINE**

GAS						NEW CAERSB MODEL DIMENSIONS			APPROX. WEIGHT	175 PSI RATING*			250 PSI RATING*		
ENGINE HP	TANK CAP (GAL.)	R-SERIES GR2-30A	PUMP MODEL	PL-SERIES* CBEPLB	PUMP MODEL	L	W	H	LBS.	RPM	CFM DISPL.	CFM DEL'Y	RPM	CFM DISPL.	CFM DEL'Y
13	NA	BGR7-H	R15B	BGPL7-H	PL15A	41.2	20.5	29.3	400	1025	29.9	23.2	950	27.7	19.8
13	(2) 4	HGR7-LPH	R15B	HGPL7-LPH	PL15A	41.3	22.3	37.6	500	1025	29.9	23.2	950	27.7	19.8
13	30	HGR7-3H	R15B	HGPL7-3H	PL15A	41.6	20.5	45.5	485	1025	29.9	23.2	950	27.7	19.8
13	60	HGR7-6H	R15B	HGPL7-6H	PL15A	52.5	21.3	49.1	585	1025	29.9	23.2	950	27.7	19.8
13	80	HGR7-8H	R15B	HGPL7-8H	PL15A	67.5	21.3	49.1	640	1025	29.9	23.2	950	27.7	19.8
14	NA	BGR7K	R15B	BGPL7K	PL15A	41.2	20.5	29.3	400	1025	29.9	23.2	950	27.7	19.8
14	(2) 4	HGR7-LPK	R15B	HGPL7-LPK	PL15A	41.3	22.3	37.6	500	1025	29.9	23.2	950	27.7	19.8
14	30	HGR7-3K	R15B	HGPL7-3K	PL15A	41.6	20.5	45.5	485	1025	29.9	23.2	950	27.7	19.8
14	60	HGR7-6K	R15B	HGPL7-6K	PL15A	52.5	21.3	49.1	585	1025	29.9	23.2	950	27.7	19.8
14	80	HGR7-8K	R15B	HGPL7-8K	PL15A	67.5	21.3	49.1	640	1025	29.9	23.2	950	27.7	19.8
20.5	NA	BGR10K	R30D	BGPL10K	PL30A	34	23	29	540	765	44.6	36.2	680	39.6	31.2
22.5	5	BGR12K	R30D	BGPL12K	PL30A	46	28	35.8	590	940	55	44.2	810	47.2	38.4

H - Honda. K - Kohler. NOTES: \*Only pressure lubricated units are capable of 250 PSIG operation. Units tested in accordance with CAGI/PNEUROPE Acceptance Test Code PN2CPTC3. Dimensions are for R-Series compressors. Add 1" to the width for PL units.

## ENGINE DRIVEN **DIESEL**

DIESEL						NEW CAERSB MODEL DIMENSIONS			APPROX. WEIGHT	175 PSI RATING*			250 PSI RATING*		
ENGINE HP	TANK CAP GAL.	R-SERIES GR2-30A	PUMP MODEL	PL-SERIES* CBEPLB	PUMP MODEL	L	W	H	LBS.	RPM	CFM DISPL.	CFM DEL'Y	RPM	CFM DISPL.	CFM DEL'Y
9.1	NA	BDR5K	R15B	BDPL5K	PL15A	41.2	20.6	29.3	440	870	25.3	20.1	650	18.9	13.6
9.1	30	HDR5-3K	R15B	HDPL5-3K	PL15A	41.6	20.5	45.5	570	870	25.3	20.1	650	18.9	13.6
9.1	80	HDR5-8K	R15B	HDPL5-8K	PL15A	67.5	21.3	49.1	680	870	25.3	20.1	650	18.9	13.6
9.1	NA	BDR5Y	R15B	BDPL5Y	PL15A	41.2	20.6	29.3	440	940	27.4	21.7	810	23.6	18.7
9.1	30	HDR5-3Y	R15B	HDPL5-3Y	PL15A	42.7	20.5	45.5	570	940	27.4	21.7	810	23.6	18.7
9.1	80	HDR5-8Y	R15B	HDPL5-8Y	PL15A	67.5	21.3	49.1	680	940	27.4	21.7	810	23.6	18.7

K - Kohler. Y-Yanmar. NOTE: Only pressure lubricated units are capable of 250 PSIG operation. Units tested in accordance with CAGI/PNEUROPE Acceptance Test Code PN2CPTC3. Dimensions are for R-Series compressors. Add 1" to the width for PL units.

### GASOLINE



**KOHLER**  
14 HP  
Command Pro  
CH440



**KOHLER**  
20 HP  
Command Pro  
CH640



**KOHLER**  
9.1 HP  
Kohler Diesel  
KD-440



**KOHLER**  
23 HP  
Command Pro  
CH680



**HONDA**  
13 HP  
GX390



**YANMAR**  
9.1 HP  
L100V