

## VR Series: Simplex

hp	kW	Model	Voltage/Phase	Mounting Config.	Tank Style	Tank Cap. (Gal.)	CFM 100 PSIG	CFM 150 PSIG	Noise Level (dBA)	Air Outlet NPT	Oil Cap. (Gal)	Weight (lbs.)	L (in.)	W (in.)	H (in.)	Starter	After cooler
7.5	5.5	VR05PURVS	208-230 1Ph 208-230/460 3Ph	Tank	Vert.	80	26.3	22.2	72	.50"	1	695	39	26	69	Yes	No
		VR05PURHS	208-230 1Ph 208-230/460 3Ph	Tank	Horiz.	80	26.3	22.2	72	.50"	1	550	66	23	43	Yes	No
10	7.5	VR07PURHS	208-230/460 3Ph	Tank	Horiz.	80	36.4	28.7	72	.75"	1	670	66	23	43	Yes	No

## VR Series: Duplex

hp	kW	Model	Voltage/Phase	Mounting Config.	Tank Style	Tank Cap. (Gal.)	CFM 100 PSIG	CFM 150 PSIG	Noise Level (dBA)	Air Outlet NPT	Oil Cap. (Gal)	Weight (lbs.)	L (in.)	W (in.)	H (in.)	Starter	After cooler
7.5	5.5	VR05PDRHS	208-230 1Ph 208-230/460 3Ph	Tank	Horiz.	120	52.6	44.4	76	.50"	1	1210	76	32	50	Yes	No
10	7.5	VR07PDRHS	208-230/460 3Ph	Tank	Horiz.	120	72.8	57.4	77	.75"	1	1325	76	32	50	Yes	No